

# Xerox® DocuMate® 4799 Scanner

## Extra Performance and Versatility for Heavy Scanning Demands

- 112 ppm / 224 ipm\* at 300 dpi
- A3 (11" x 17") paper size
- ADF holds 350 pages†
- 3 Ultrasonic double feed detection sensors
- Create searchable PDF files to make it easy to find scanned documents
- Pre- & Post-Scan Imprinter (sold separately)
- Color Space Compatibility with Xerox® iGen® digital press
- Xerox® FreeFlow Makeready® application Supported

\* Landscape A4, b&w, gray & color  
† 20 lb., 75-80 g/m<sup>2</sup> paper

**Document Manager Magazine's  
2015 Product of the Year,  
and 2016 High Volume Imaging  
Product of the Year.**

### Overcome Your Fear of Difficult Documents

Versatility, high-speed and superior reliability make the Xerox® DocuMate® 4799 a powerful scanner for demanding environments. With up to a 40,000 page per day duty cycle, this innovative workhorse scans up to 112 pages per minute and employs three advanced sensor systems: ultrasonic double feed detection, stapled document detection and intelligent feed control to ensure that your scan job will not get interrupted.

Documents of various sizes can be stacked together in the automatic feed tray without worry because the Xerox® DocuMate® 4799 employs not one, but three ultrasonic double feed detection sensors to cover the entire width of a document. The scanner also detects stapled multi-page documents and halts the scanning process—minimizing damage to the optical glass and your documents. The thickness of documents being fed into the scanner is also monitored, automatically adjusting the roller pressure to ensure that all pages are accurately fed. This combination of sensors creates one of the most reliable feed mechanisms available today.

Up to 350 mix-sized documents can be stacked in the center of the automatic feeder. There is no need to organize documents according to their size, so scanning is fast, easy and efficient. A pre- and post-scan imprinter is also available for the Xerox® DocuMate® 4799 and is supported through the included TWAIN™ and ISIS® drivers.

### Advanced Image Processing Technology

The Xerox® DocuMate® 4799 provides both high quality Image Enhancement and increased productivity when combined with Visioneer Acuity – the ‘Corrective lenses for your scanner’. With all of the image cleanup and enhancement features of Kofax® VRS™ Pro and Visioneer Acuity, the result is a finely tuned, sharp, and clear image every time you scan. Advanced features like Auto Color Detection, Auto Rotation, Blank Page Removal are included with the software. No ‘Upgrade now for more features’ is required. We provide it all. Combine this with Visioneer’s industry-leading TWAIN™ driver technology, DriverPlus, and you get the most robust, fully-featured high quality scanning solution in its class. Integration with industry standard TWAIN capable capture applications becomes a breeze, as every single Acuity feature is readily accessible through the drivers elegant yet user friendly interface.

The Xerox® DocuMate® 4799 is very easy to maintain. Its unique “clamshell” design allows full access to the entire paper path so you can clean the unit without calling a service technician. It is quick and easy to replace the rollers, inspect the path and get back to scanning. This reduces the amount of downtime and improves the unit’s cost effectiveness.

Designed for document capture and workflow the Xerox® DocuMate® 4799 delivers everything you ever wanted in a high-speed document scanner: productivity, reliability and innovation.



# Xerox® DocuMate® 4799 Scanner Software Solutions

## Image Enhancement Technology

Visioneer® OneTouch® works seamlessly with Visioneer Acuity or Kofax VRS. Both integrate with OneTouch via the Visioneer DriverPlus TWAIN drivers, which allows basic settings to be applied from within the OneTouch interface. Using advanced algorithms and dynamic thresholding, they effectively improve the visual clarity of every scan, applying intelligent correction to imperfect images, increasing OCR accuracy, and saving time.

## Nuance® Searchable PDF Solution

Nuance OmniPage® and PDF Converter provide everything you need to create, convert, edit, assemble and securely share searchable PDF files with precision OCR analysis, advanced layout detection and Logical Form Recognition™ (LFR) technology. Combining powerful functionality, superior Microsoft® Office® support and DMS integration into one package.

## Office Gemini Dokmee Capture

Dokmee Capture production scanning software provides all the features required for document capture, processing and reporting. It allows businesses both large and small to easily convert their scanned documents into digital files, capture images and information contained in them, and then organize it all into searchable data. This mission-critical business information is then placed into a centralized location to be easily searched, stored and retrieved when needed.

Xerox® DocuMate® 4799 Product Specifications	
Model Number w/VRS Pro (US)	XDM47995D-WU
Model Number w/VRS Basic (US)	XDM47995D-VRS/B
Model Number w/VRS Pro (Euro/UK)	XDM47995E-WU
Model Number w/VRS Basic (Euro/UK)	XDM47995E-VRS/B
Scan Speed	112 ppm / 224 ipm (color, grayscale, or b&w @ 150, 200, or 300 dpi, landscape A4)
Scan Method	Automatic Document Feeder (ADF)
Imaging Sensor	Dual Color CIS detector
Light Source	Xenon Lamp
Background	Switchable black or white background
Optical Resolution	600 dpi
Output Bit Depth	24-bit color, 8-bit grayscale, 1-bit black & white
Other Functions	Length control, barcode detection, patch code detection, Automatic separation, control sheet, long paper mode
Interface	Hi-speed USB 2.0 (1.1 compatible)
Detection	Ultrasonic double feed detection (3 positions), stapled document detection
Accessories	DocuMate 4700 flatbed scanner, Pre- & Post-Scan Imprinter
ADF Minimum Document Size	1.9" x 2.8" (48 mm x 70 mm)
ADF Maximum Document Size	11.9" x 17" (302 x 432 mm); custom lengths up to 100" (2540 mm)
ADF Capacity	Up to 350 sheets (20 lb., 75-80 g/m <sup>2</sup> paper)
Document Weight	Thin mode: 5 - 13 lbs. (20 - 50 g/m <sup>2</sup> )
	Normal mode: 13 - 42 lbs. (50 - 157 g/m <sup>2</sup> )
	Thick mode: 42 - 56 lbs. (157 - 209 g/m <sup>2</sup> )
	Auto mode: 5 - 42 lbs. (20 - 157 g/m <sup>2</sup> )
Document Thickness	1.9 - 7.9 mils (0.04 - 0.2 mm) Straight path: max. 23.6 mils (0.6 mm) Note: 1 mil = 0.001"
Duty Cycle	40,000 pages/day
Power Requirement	AC 100 – 240 V, 50/60 Hz
Power Consumption	150 watts while scanning
	50 watts in Ready / Waiting Mode
	2 watts or less in Sleep Mode
Operating Environment	Temperature: 59°F - 86°F (15°C - 30°C)
	Humidity: 10 - 80% RH
Storage Environment	Temperature: 32°F - 104°F (0°C - 40°C)
	Humidity: 30 - 80 % RH
Dimensions	18.7"(w) x 23"(d) x 13"(h) (474 x 585 x 329 mm)
Weight	55 lbs. (25 kg)

For more information about the Xerox line of scanners, visit [www.xeroxscanners.com](http://www.xeroxscanners.com)



©2016 Xerox Corporation. All rights reserved. Xerox®, Xerox and Design®, DocuMate®, FreeFlow Makeready® and iGen® are registered trademarks of Xerox Corporation in the United States and other countries, and are used under license from Xerox Corporation. Visioneer® is an authorized trademark licensee of Xerox®. Visioneer® and Visioneer OneTouch® are trademarks of Visioneer, Inc. Kofax®, VirtualReScan® and VRS™ are trademarks of Kofax, Inc. Nuance® and OmniPage® are trademarks of Nuance Communications, Inc. or its affiliates in the United States and/or other countries. Dokmee Capture® is a registered trademark of Office Gemini. Microsoft®, Windows Vista®, Windows®, the Windows logo and XP® are trademarks of Microsoft Corporation in the United States and/or other countries. Intel® and Pentium® are trademarks of Intel Corporation in the U.S. and/or other countries. TWAIN™ is a trademark of TWAIN Working Group. EMC®, Captiva®, and ISIS® are trademarks of EMC Corporation. ENERGY STAR® and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Universal Serial Bus is a trademark of USB Implementers Forum, Inc. (USB-IF). All other trademarks are the property of their respective owners and are hereby acknowledged. Prices, features, specifications, capabilities, appearance and availability of Xerox® products and services are subject to change without notice. 12/16 BR20577

### Box Contents

- DocuMate 4799 Scanner
- Quick Installation Guide
- Technical Support Card
- Blower w/Brush
- Roller Cleaning Paper, Cleaning Paper Card
- Shading Sheet, Shading Caution Leaflet
- DFP (Double Feed Prevention) Roller
- AC Power Cord US (1), Euro/UK (2)
- USB Cable
- DVD-ROM including:
  - User's Manual
  - Kofax VRS Pro (with AIPE-EBC) or with VRS Basic depending on SKU<sup>Y</sup>
  - Nuance® OmniPage® Pro
  - Nuance PDF Converter
  - Office Gemini Dokmee Capture
  - Visioneer OneTouch
  - Visioneer Acuity
  - Scanner Drivers: DriverPLUS TWAIN™, Microsoft Windows® Image Acquisition (WIA), EMC Captiva ISIS®

### PC Minimum System Requirements

- Intel® Pentium® 4 or equivalent processor
- Windows 10 / 8 / 7 / Vista® / XP®
- 2GB RAM
- 350 MB available hard disk space
- DVD-ROM drive
- USB port

### Warranty Information

- 90-Day Advance Exchange Warranty
- Optional 1-5 year Advance Exchange
- Optional 1-5 year Next Day Business \*\*
- Optional 1-5 year 4-hour response \*\*

### Consumables:

- 4799ROLL-KIT - User installable roller assembly. Roller kits last up to 400,000 scans, depending on scanning conditions.

\*\*Includes 1 preventive maintenance visit per year. Coverage is available Monday through Friday 8:00 am to 5:00 pm (local time), excluding US holidays.

\*\*\* Dokmee Capture is not supported on Microsoft Windows XP

<sup>Y</sup> Kofax VRS 4.5 is not supported on Microsoft Windows 8 and above

